

FLG 245HV-GREEN TRACKING

The indoor alignment pro  green laser



TECHNICAL DATA		FLG 245HV-GREEN TRACKING	FEATURES
Self-levelling		horizontal/vertical	<ul style="list-style-type: none"> · Working range up to 1000 m diameter · Dust / water protection IP 54 · Variable scanning and laser point mode · Permanent 90° plumb beam · Automatic TILT alarm function · Auto-shut-off when out of level · Manual slope setting of X and Y axis · Remote control function (on/off) · Floor mount with centring mark for accurate set up · above a ground point
Grade		manual	
Self-levelling range		±5°	
Laser class		2	
Visible laser beam		green	
Accuracy horizontal		1,0 mm / 10 m	
Accuracy vertical		1,5 mm / 10 m	
Working range with FR 77-MM Tracking		1000 m	
Rotating w/o receiver / Ø		40 m	
Scanning w/o receiver / radius		60 m	
Tracking function		yes	
Working range tracking function		60 m	
Scanning		2 step	
Laserdot mode		yes	
90° plumb beam up		yes	
Slope setting manual X-Axis		±5° (±9%)	
Y-Axis		±5° (±9%)	
Automatic TILT function		yes	
Working range remote control		IR 100 m	
Remote control function (on/off)		yes	
Rotating speed rpm		300, 800	
Operating time		24 h NiMH	
Temperature range		-20° to +50°C	
Dust / water protection		IP 54	
SUPPLIED WITH FLG 245HV-GREEN TRACKING			ART.-NO. 244701 <ul style="list-style-type: none"> · Receiver FR 77-MM Tracking with clamp for levelling staff · Remote control · Rechargeable batteries · Charger · Battery case for alkaline batteries · Wall mount · Floor mount · Magnetic target · Laser glasses · Carrying case