





Cole-Parmer LB-400-600i Precision Toploading Balance with LCD, 600g x 1mg, Internal Calibration

Cole-Parmer - Item # EW-10102-28

No Reviews [Write the First Review](#)

Quality and precision at an economical price

- 5-year industry-leading warranty
- Large, backlit LCD provides clear visibility of weighing results
- Internal and external calibration options
- Removable draft shield on milligram (0.001g) readability options
- USB, RS-232, Ethernet, and Wi-Fi† interfaces
- Filter settings can be easily adjusted depending on the working environment
- Multiple working modes handle a variety of weighing functions
- Fast stabilization and response time
- Quick stabilization time of 2 seconds
- 5 year warranty



PRODUCT OPTIONS

Specifications & Description

| | |
|--------------------------|---|
| Capacity (g) | 600 |
| Capacity (kg) | 0.6 |
| Capacity (lbs) | 1.32 |
| Readability (mg) | 1 |
| Readability (g) | 0.001 |
| Repeatability (mg) | 2 |
| Repeatability (g) | 0.002 |
| Linearity (mg) | 3 |
| Linearity (g) | 0.003 |
| Weighing Units | g, mg, kg, ct, lb, oz, ozt, dwt, tlh, tls, tlt, tlc, mom, gr, N, ti, baht, tola, msg |
| Calibration Type | Internal |
| Languages | English, Polish, Russian, Spanish, French, German, Italian, Czech, Chinese, Arabic, Turkish, Korean |
| Output | 2 x RS 232, USB-A, USB-B, Ethernet, Wi-Fi |
| USB Interface | Yes |
| RS-232 Interface | Yes |
| Stability Indicator | Yes |
| Stabilization Time (Sec) | 2 |
| Auto Shutoff | Yes |
| Low Battery Indicator | No |
| Battery | No |
| Power (VAC) | 100 to 240 |
| Length (in) | 13 1/10 |
| Height (in) | 7 1/8 |
| Width (in) | 8 1/10 |
| Pan Length (in) | 5 |



KEY FEATURES

- 5-year industry-leading warranty
- Large, backlit LCD provides clear visibility of weighing results
- Internal and external calibration options
- Removable draft shield on milligram (0.001g) readability options
- USB, RS-232, Ethernet, and Wi-Fi† interfaces
- Filter settings can be easily adjusted depending on the working environment
- Multiple working modes handle a variety of weighing functions
- Fast stabilization and response time
- Quick stabilization time of 2 seconds
- 5 year warranty

MORE ABOUT THIS ITEM

The Cole-Parmer LT series of precision toploading balances provide advanced weighing features at an economical price. The large, stainless steel weigh pan allows for easy weighing of large items. Easy to operate, the balances are calibrated either internally or externally using a calibration mass. The large, backlit LCD allows a clear presentation of the weighing results. To achieve the best possible weighing conditions, the balances feature a filter level setting that can be adjusted to a fast or slow mode depending on the working environment. Other features include quick access keys, balance taring, balance zeroing, auto switch-off, and backlight turn-off time.

The balance features several databases for recording users, products, weighings, and tares. Only users with appropriate access can adjust balance settings, export data, import data, and delete records. Two USB, two RS-232 interfaces, Ethernet, and Wi-Fi† port offer external connection to a computer or printer for GLP/GMP-compliant output.

†Only models with internal calibration feature Wi-Fi interface.

| | |
|--------------------------|---|
| Pan Width (in) | 5 |
| Draft Shield Height (in) | 3 11/64 |
| Draft Shield Width (in) | 6 19/64 |
| Draft Shield Depth (in) | 6 19/64 |
| Min Temperature (° C) | 10 |
| Max Temperature (° C) | 40 |
| Description | Precision Toploading Balance with LCD, 600g x 1mg, Internal Calibration |
| Warranty | 5 Years |

Cole-Parmer | 625 East Bunker Ct Vernon Hills, IL 60061 United States
Telephone: 1-847-549-7600 | Fax: 847-549-1700 | Email: export@coleparmer.com
© 2024 Cole-Parmer Instrument Company, LLC. All Rights Reserved.