



Cole-Parmer Industrial Bimetal Thermometer, 3" Dial, Adjustable Angle, 9" Stem, 0-250°F (-20-120°C)

Cole-Parmer - Item # EW-90590-28

No Reviews [Write the First Review](#)

NEMA 4X/IP66 protection with all-welded stainless steel construction for the toughest of jobs

- Hermetically sealed case prevents entry of moisture, interior corrosion and coil freeze up
- Anti-parallax dial for precise readings of both scales
- Silicone-dampened coil reduces pointer flutter and improves response time during high vibration applications
- Adjustable-angle connection can be rotated 360 degrees
- External adjustment reduces maintenance
- NEMA 4X/IP66 protection
- 5 year warranty

PRODUCT OPTIONS

Specifications & Description

| | |
|-----------------------|---|
| Min Temperature (° F) | 0 |
| Min Temperature (° C) | -20 |
| Height (in) | 12 7/8 |
| Max Temperature (° F) | 250 |
| Max Temperature (° C) | 120 |
| Accuracy | ±1% |
| Division (° C) | 2 |
| Division (° F) | 2 |
| Thermometer Fill | No Fill |
| Dial Size (in) | 3 |
| Dial / Case Material | 304 SS |
| Overall Length (in) | 12.875 |
| Overall Length (mm) | 327.025 |
| Immersion Depth (mm) | 2 |
| Stem Length (in) | 9 |
| Stem Diameter (in) | 0.25 |
| Stem Material | 304 SS |
| Connection | 1/2" NPT (M) |
| ASTM Number | ASME B40.3 |
| Description | Industrial Bimetal Thermometer, 3" Dial, Adjustable Angle, 9" Stem, 0/250F & -20/120C |
| Warranty | 5 years |



KEY FEATURES

- Hermetically sealed case prevents entry of moisture, interior corrosion and coil freeze up
- Anti-parallax dial for precise readings of both scales
- Silicone-dampened coil reduces pointer flutter and improves response time during high vibration applications
- Adjustable-angle connection can be rotated 360 degrees
- External adjustment reduces maintenance
- NEMA 4X/IP66 protection
- 5 year warranty

MORE ABOUT THIS ITEM

Use these industrial dual-scale thermometers for a wide variety of applications from petroleum plants to food and beverage. Various temperature ranges and dial sizes can accommodate anyone. Each thermometer can perform quick and limited span adjustments. Dry; no liquid fill.

Cole-Parmer | 625 East Bunker Ct Vernon Hills, IL 60061 United States

Telephone: 1-847-549-7600 | Fax: 847-549-1700 | Email: export@coleparmer.com

© 2024 Cole-Parmer Instrument Company, LLC. All Rights Reserved.