



Cole-Parmer TB-800-220 Analytical Balance with Touchscreen, 220g x 0.1mg, External Calibration

Cole-Parmer - Item # EW-10102-13

No Reviews [Write the First Review](#)

Weighing surface allows for precise weighing of small items

- Five-year industry-leading warranty
- IR proximity touchless sensors offer touch-free balance control
- Color capacitive touch-screen display provides clear visibility of weighing results
- USB, RS-232, Ethernet, and Wi-Fi interfaces offer secure data connections
- Autotest GLP function quickly diagnoses weighing errors
- Adjustable filter settings help optimize performance depending on the working environment
- Menu screen can be customized to match your everyday needs
- Statistics working mode quickly analyzes data from series of measurements
- Multiple working modes handle a variety of weighing functions
- Menu descriptions can be displayed in multiple languages
- Fast stabilization and response time
- Spacious weighing chamber allows for tool-free disassembly and assembly
- Anti-static coating on weighing chamber panes (0.01mg and 0.1mg four place readability)
- 5 year warranty



PRODUCT OPTIONS



Agents Offline

Specifications & Description

Capacity (g)	220
Readability (mg)	0.1
Readability (g)	0.0001
Repeatability (mg)	0.07
Repeatability (g)	7E-05
Linearity (mg)	0.2
Linearity (g)	0.0002
Weighing Units	g, mg, ct, lb, oz, ozt, dwt, tln, tln, tlt, tlc, mom, gr, ti, N, b, aht, tola, msg, u1, u8
Calibration Type	External
Languages	English, Arabic, Chinese, Czech, French, German, Italian, Korean, Polish, Russian, Spanish, Turkish
Output	2 x USB-A, USB-B, RS-232, Wi-Fi, Ethernet
USB Interface	Yes
RS-232 Interface	Yes
Stability Indicator	Yes
Height (in)	14
Width (in)	8
Depth (in)	14
Pan Diameter (in)	3 1/2
Draft Shield Height (in)	9
Draft Shield Width (in)	7 1/2
Draft Shield Depth (in)	7
Description	Analytical Balance with Touchscreen, 220g x 0.1mg, External Calibration
Warranty	5 Years



INCLUDES

Glass draft shield, draft ring, AC adapter, and power cord.

KEY FEATURES

- Five-year industry-leading warranty
- IR proximity touchless sensors offer touch-free balance control
- Color capacitive touch-screen display provides clear visibility of weighing results
- USB, RS-232, Ethernet, and Wi-Fi interfaces offer secure data connections
- Autotest GLP function quickly diagnoses weighing errors
- Adjustable filter settings help optimize performance depending on the working environment
- Menu screen can be customized to match your everyday needs
- Statistics working mode quickly analyzes data from series of measurements
- Multiple working modes handle a variety of weighing functions
- Menu descriptions can be displayed in multiple languages
- Fast stabilization and response time
- Spacious weighing chamber allows for tool-free disassembly and assembly
- Anti-static coating on weighing chamber panes (0.01mg and 0.1mg four place readability)
- 5 year warranty

MORE ABOUT THIS ITEM

The Cole-Parmer series of analytical balances feature a removable glass draft shield with three doors for easy cleanup and access to the weighing pan. The balances are calibrated either internally or externally using a calibration mass. The 4-1/4" x 2-1/2" color capacitive touch-screen display features a status bar, weighing result window, editable information fields, and editable tool bar. The area beneath weight indication display can be customized to meet your personal programming needs.

Two built-in infrared (IR) proximity sensors can be programmed with different functions for each working mode enabling touch-free balance control, while minimizing cross-contamination. Working modes include weighing, parts counting, check weighing, dosing, percent weighing, density of solids, density of liquids, animal weighing, statistics, peak hold, and formulations. Other features include adjustable filter level settings, quick-access keys, balance taring, balance zeroing, auto switch-off, and backlight turn-off time.

The balances feature several databases for recording products, users, packaging, customers, formulations, formulation reports, ambient conditions, and weighing. Only users with appropriate access can add new records, export data, import data, delete records, and print saved data. RS-232, 2×USB-A (interchangeable), USB-B, Ethernet, and Wi-Fi† offer external connection to a computer or printer for GLP/GMP-compliant output. The autotest GLP function provides an enhanced balance summary to aid in assessing operation and diagnosing reasons for occurrence of errors in weighing.

†Only models with internal calibration feature Wi-Fi interface.

Cole-Parmer | 625 East Bunker Ct Vernon Hills, IL 60061 United States
Telephone: 1-847-549-7600 | Fax: 847-549-1700 | Email: export@coleparmer.com
© 2024 Cole-Parmer Instrument Company, LLC. All Rights Reserved.