

# Vertical Pressure Steam Sterilizer

## Characteristics:



1. Automatically controlled by computer, digital display of working status, touch type key.
2. Fully automatically route for water inlet, pulse vacuum, heating, sterilizing, draining, exhausting, vacuum drying.
3. 3 times pulse vacuum, which make the vacuum rate as -0.081mpa, and ensure the high extracting of inner air from dressing, A.B type hollowed appliance.
4. With 4 fixed program for appliance, medical dressing, rubbers and fluid, and the user can also set the program as they need.
5. Equipped with the PT/TT testing connector, easy to run the testing.
6. Multiple pulse vacuum drying after sterilizing, ensure the nice sterilizing.
7. Equipped with bacteria filter, ensure the sterile air enter the inner vacuum environment, avoid the second contamination.
8. Steam-water inner circulation system: no steam discharge, and the environment for sterilizing will be clean and dry.
9. Automatically shut off with beep reminding after sterilization.

## Main Technical Parameters:

Model	FSF-35HV	FSF-50HV	FSF-75HV	FSF-100HV
Capacity	35L (φ318×450)mm	50L (φ340×550)mm	75L (φ400×600)mm	100L (φ440×650)mm
Working pressure	0.22Mpa			
Working temperature	134°C			
Max.working pressure	0.23Mpa			
Heat average	≤±1°C			
Time	1~99 min			
Temp.range	0~134°C			
Power	2.5KW/AC220V.50Hz	3KW/AC220V.50Hz	4.5KW/AC220V.50Hz	4.5KW/AC220V.50Hz
Exterior size	6004101030mm	6904701140(mm)	7305101270(mm)	7505501305(mm)
Packing size	7305001170(mm)	7605501290(mm)	8206001380(mm)	8406401410(mm)
G.W/N.W	96kg/77kg	120kg/100kg	140kg/118kg	160kg/128kg