

Horizontal Cylindrical Pressure Steam Sterilizer (microcomputer control)

Characteristics:

1. Sterilizing course automatic sterilization controlled by computer, easy to operate.
2. With drying function, suitable dressing drying.
3. With over-temperature, over-pressure auto-protect device.
4. The door opening mechanism cannot be operated until the pressure in the chamber is reduced to 0.027MPa. It can't be start on if the doesn't closed well.
5. The safety valve will be open automatically when the inner pressure over 0.24MPa, and the steam be exhausting to the water tank.
6. The power will be cut-off automatically, cut-off the water and alarm when the machine lacking water.
7. The chamber of the sterilizer is made of stainless steel.
8. With printer.



Model	Capacity	Working pressure	Working temperature	Temp. range	Timer	Time of drying	Heat average	Power	Exterior size(cm)	Packing size(cm)	G.W/N.W
FSF-150YDB	150L Φ440×1000mm	0.22Mpa	134°C	40°C-134°C	0-99 min	0-99min	±2°C	9KW/380V 50Hz	140×65×160	156×82×182	430kg/340kg
FSF-200YDB	200L Φ515×1000mm							9KW/380V 50Hz	140×75×170	156×91×188	436kg/350kg
FSF-280YDB	280L Φ600×1000mm							12KW/380V 50Hz	152×91×190	168×108×210	570kg/462kg

Table Top Steam Sterilizer

1. Sterilizing course automatic sterilization controlled by computer, easy to operate.
2. With drying function, suitable dressing drying.
3. With over-temperature, over-pressure auto-protect device.
4. The door opening mechanism cannot be operated until the pressure in the chamber is reduced to 0.027MPa. It can't be start on if the doesn't closed well.
5. The safety valve will be open automatically when the inner pressure over 0.24MPa, and the steam be exhausting to the water tank.
6. The power will be cut-off automatically, cut-off the water and alarm when the machine lacking water.
7. The chamber of the sterilizer is made of stainless steel.
8. With printer.



Model	FSF-XB20J	FSF-XB24J
Capacity	20L (Φ250×420)mm	24L (Φ250×520)mm
Working pressure	0.22Mpa	
Working temperature	134°C	
Temp. range	105°C-134°C	
Timer	0-60 min	
Heat average	1°C	
Power	1.5KW/AC220V.50Hz(AC110V 60Hz)	
Sterilizing plate	340×200×30mm(3 pieces)	400×200×30mm(3 pieces)
Exterior size	480×480×384mm	580×480×384mm
Packing size	700×580×500mm	800×580×500mm
G.W/N.W	44kg/40kg	50kg/45kg