

Home | Laboratory Equipment | Magnetic Stirrers and Hot Plates | Cole-Parmer® ST-200 Series Multiposition Stirrers | "Cole-Parmer ST-200-MP9 Nine-Position Stirrer, 230V"



Cole-Parmer ST-200-MP9 Nine-Position Stirrer, 230V

Cole-Parmer - Item # EW-51450-28

No Reviews Write the First Review

Versatile—perform different mixing applications at the same time

- Each stirring position is individually controlled
- Capable of stirring solutions from 100 to 1500 rpm
- Designed to keep spills away from the electronics
- Solid ceramic top offers excellent corrosion and chemical resistance
- 3 year warranty

PRODUCT OPTIONS





OFTEN BOUGHT WITH



Cole-Parmer® Essentials Glass Erlenmeyer Flasks, Graduated, Heavy Rim

VIEW ALL 13

Specifications & Description

Top Plate Length (in) 12 Top Plate Width (in) 12 Top Plate Length (cm) 30.5 Top Plate Width (cm) 30.5 Top Plate Material Ceramic Max Load Capacity (lbs) Max Load Capacity (kg) 18.14 Low Speed (rpm) 100 High Speed (rpm) 1500 No. Of Stirring Positions 9 Max Stirring Volume per position (Liters) Length (in) 17 1/2 Width (in) 12 Height (in) 4 1/2 Length (cm) 44.45 Width (cm) 30.48 Height (cm) Power (VAC) Power (Hz) Power (amps) Description Nine-Position Stirrer, 230 VAC Warranty 3 Years	·	-
Top Plate Length (cm) 30.5 Top Plate Width (cm) 30.5 Top Plate Material Ceramic Max Load Capacity (lbs) 40 Max Load Capacity (kg) 18.14 Low Speed (rpm) 100 High Speed (rpm) 1500 No. Of Stirring Positions 9 Max Stirring Volume per position (Liters) Length (in) 17 1/2 Width (in) 12 Height (in) 41/2 Length (cm) 44.45 Width (cm) 30.48 Height (cm) 11.43 Power (VAC) 230 Power (Hz) 50 Power (amps) 2.25 Description Nine-Position Stirrer, 230 VAC	Top Plate Length (in)	12
Top Plate Width (cm) 30.5 Top Plate Material Ceramic Max Load Capacity (lbs) 40 Max Load Capacity (kg) 18.14 Low Speed (rpm) 100 High Speed (rpm) 1500 No. Of Stirring Positions 9 Max Stirring Volume per position (Liters) Length (in) 17 1/2 Width (in) 12 Height (in) 41/2 Length (cm) 44.45 Width (cm) 30.48 Height (cm) 11.43 Power (VAC) 230 Power (Hz) 50 Power (amps) 2.25 Description Nine-Position Stirrer, 230 VAC	Top Plate Width (in)	12
Top Plate Material Ceramic Max Load Capacity (lbs) 40 Max Load Capacity (kg) 18.14 Low Speed (rpm) 100 High Speed (rpm) 1500 No. Of Stirring Positions 9 Max Stirring Volume per position (Liters) Length (in) 17 1/2 Width (in) 12 Height (in) 41/2 Length (cm) 44.45 Width (cm) 30.48 Height (cm) 11.43 Power (VAC) 230 Power (Hz) 50 Power (amps) 2.25 Description Nine-Position Stirrer, 230 VAC	Top Plate Length (cm)	30.5
Max Load Capacity (lbs) 40 Max Load Capacity (kg) 18.14 Low Speed (rpm) 100 High Speed (rpm) 1500 No. Of Stirring Positions 9 Max Stirring Volume per position (Liters) Length (in) 17 1/2 Width (in) 12 Height (in) 41/2 Length (cm) 44.45 Width (cm) 30.48 Height (cm) 11.43 Power (VAC) 230 Power (Hz) 50 Power (amps) 2.25 Description Nine-Position Stirrer, 230 VAC	Top Plate Width (cm)	30.5
Max Load Capacity (kg) Low Speed (rpm) High Speed (rpm) No. Of Stirring Positions Max Stirring Volume per position (Liters) Length (in) 17 1/2 Width (in) Height (in) 4 1/2 Length (cm) Width (cm) Height (cm) 11.43 Power (VAC) Power (Hz) Description Nine-Position Stirrer, 230 VAC	Top Plate Material	Ceramic
Low Speed (rpm) 100 High Speed (rpm) 1500 No. Of Stirring Positions 9 Max Stirring Volume per position (Liters) 0.5 Length (in) 17 1/2 Width (in) 12 Height (in) 4 1/2 Length (cm) 44.45 Width (cm) 30.48 Height (cm) 11.43 Power (VAC) 230 Power (Hz) 50 Power (amps) 2.25 Description Nine-Position Stirrer, 230 VAC	Max Load Capacity (lbs)	40
High Speed (rpm) No. Of Stirring Positions Max Stirring Volume per position (Liters) Length (in) 17 1/2 Width (in) 12 Height (in) 4 1/2 Length (cm) 44.45 Width (cm) 30.48 Height (cm) 11.43 Power (VAC) Power (Hz) Description Nine-Position Stirrer, 230 VAC	Max Load Capacity (kg)	18.14
No. Of Stirring Positions Max Stirring Volume per position (Liters) Length (in) 17 1/2 Width (in) 12 Height (in) 4 1/2 Length (cm) 44.45 Width (cm) 30.48 Height (cm) 11.43 Power (VAC) Power (Hz) Description Nine-Position Stirrer, 230 VAC	Low Speed (rpm)	100
Max Stirring Volume per position (Liters) 0.5 Length (in) 17 1/2 Width (in) 12 Height (in) 4 1/2 Length (cm) 44.45 Width (cm) 30.48 Height (cm) 11.43 Power (VAC) 230 Power (Hz) 50 Power (amps) 2.25 Description Nine-Position Stirrer, 230 VAC	High Speed (rpm)	1500
position (Liters) Length (in) 17 1/2 Width (in) 12 Height (in) 4 1/2 Length (cm) 44.45 Width (cm) 30.48 Height (cm) 11.43 Power (VAC) 230 Power (Hz) 50 Power (amps) 2.25 Description Nine-Position Stirrer, 230 VAC	No. Of Stirring Positions	9
Width (in) 12 Height (in) 4 1/2 Length (cm) 44.45 Width (cm) 30.48 Height (cm) 11.43 Power (VAC) 230 Power (Hz) 50 Power (amps) 2.25 Description Nine-Position Stirrer, 230 VAC		0.5
Height (in) Length (cm) 4 1/2 Length (cm) 44.45 Width (cm) 30.48 Height (cm) 11.43 Power (VAC) 230 Power (Hz) 50 Power (amps) 2.25 Description Nine-Position Stirrer, 230 VAC	Length (in)	17 1/2
Length (cm) 44.45 Width (cm) 30.48 Height (cm) 11.43 Power (VAC) 230 Power (Hz) 50 Power (amps) 2.25 Description Nine-Position Stirrer, 230 VAC	Width (in)	12
Width (cm) 30.48 Height (cm) 11.43 Power (VAC) 230 Power (Hz) 50 Power (amps) 2.25 Description Nine-Position Stirrer, 230 VAC	Height (in)	4 1/2
Height (cm) 11.43 Power (VAC) 230 Power (Hz) 50 Power (amps) 2.25 Description Nine-Position Stirrer, 230 VAC	Length (cm)	44.45
Power (VAC) 230 Power (Hz) 50 Power (amps) 2.25 Description Nine-Position Stirrer, 230 VAC	Width (cm)	30.48
Power (Hz) 50 Power (amps) 2.25 Description Nine-Position Stirrer, 230 VAC	Height (cm)	11.43
Power (amps) 2.25 Description Nine-Position Stirrer, 230 VAC	Power (VAC)	230
Description Nine-Position Stirrer, 230 VAC	Power (Hz)	50
VAC	Power (amps)	2.25
Warranty 3 Years	Description	
	Warranty	3 Years



MORE ABOUT THIS ITEM

These analog multiposition stirrers offer more versatility than single-position stirrers. Stirring positions are individually controlled so you can perform different mixing applications simultaneously. Each stirrer position can stir solutions from 100 to 1500 rpm. The solid ceramic top surface is corrosion and chemical resistant, is easy to clean, and measures $30.5 \times 30.5 \text{ cm}$ ($12\text{"} \times 12\text{"}$).

Cole-Parmer | 625 East Bunker Ct Vernon Hills, IL 60061 United States
Telephone: 1-847-549-7600 | Fax: 847-549-1700 | Email: export@coleparmer.com
© 2024 Cole-Parmer Instrument Company, LLC. All Rights Reserved.