



## Cole-Parmer Analog Ultrasonic Cleaner with Heat, 1.25 gal, 220 VAC

Cole-Parmer – Item # EW-59989-38

No Reviews [Write the First Review](#)

Protect sensitive items—safety shutoff and temperature-selectable alarm light for units with heat

- Easily preselect run time and temperature with rotary dials
- Obtain uniform sound waves and cleaning from the sweep function
- Activate the pulse function for 20% increase in ultrasonic power and soil removal
- Heated cleaner with a capacity of 1.25 gal
- Standard EU power
- 3 year warranty parts & labor

### PRODUCT OPTIONS

# Specifications & Description

Capacity (Gal)	1.25
Capacity (Liters)	4.73
Tank Length (in)	4 21/32
Tank Width (in)	9 7/16
Tank Height (in)	3 29/32
Tank Length (cm)	11.8
Tank Width (cm)	24
Tank Height (cm)	9.9
Length (in)	6 15/16
Width (in)	10 13/32
Height (in)	10 19/32
Length (cm)	17.6
Width (cm)	26.3
Height (cm)	26.9
Power (VAC)	220
Power (Hz)	50
No. of Transducers	1
Frequency Output (KHz)	37
Description	Ultrasonic Cleaner with Heat, 1.25 gal, 220 VAC
Warranty	3 Years



## INCLUDES

Power supply and power cord with country-specific plug.

## KEY FEATURES

- Easily preselect run time and temperature with rotary dials
- Obtain uniform sound waves and cleaning from the sweep function
- Activate the pulse function for 20% increase in ultrasonic power and soil removal
- Heated cleaner with a capacity of 1.25 gal
- Standard EU power
- 3 year warranty parts & labor

## MORE ABOUT THIS ITEM

The analog series of ultrasonic cleaners feature simple control with superior cleaning technology. Select heating temperature from 30 to 80°C, in 5° increments, with a rotary dial. Choose a maximum temperature for sensitive items and instruments—LED light illuminates if reached. Heating is not available on items 59989-29 and -30. The cleaners can be set to operate continuously or in timed runs, from 1 to 30 minutes (dial-selected). The integrated sweep mode ensures even sound distribution throughout the bath at 37 kHz for efficient and effective cleaning. Turn on pulse mode to increase ultrasonic power 20%—ideal for those hard to remove soils and pastes. Safety features include auto-shutoff if running for 8 hours continuously or if bath temperature exceeds 90°C, and a sealed display and elevated feet to protect against splashes and spills. Baths with capacities above 1 gallon also feature a side-mounted drain for easy emptying and cleaning.

**Cole-Parmer** | 625 East Bunker Ct Vernon Hills, IL 60061 United States

Telephone: 1-847-549-7600 | Fax: 847-549-1700 | Email: [export@coleparmer.com](mailto:export@coleparmer.com)

© 2024 Cole-Parmer Instrument Company, LLC. All Rights Reserved.



Agents Offline