

Bolt Gauge Transducers

Bolt Gauge Transducers

A complete range of magnetic Bolt Gauge Transducers for use with the **BG80DL** & **BG80TDL** models.



Part Number	Probe Diameter	Element Type	Probe Characteristic	Damping	Connector Type		Suitable for measuring
					Microdot	Top	All Metals
2.25 MHz Bolt Gauge Transducers							
TX2M25CM-5	1/4"	Si/EI Non-Magnetic	Standard	S	•	•	•
TX2M25CM-6	1/4"	Si/EI Magnetic	Standard	S	•	•	•
TX2M25DM	3/8"	Si/EI Magnetic	Standard	S	•	•	•
TX2M25EM-5	1/2"	Si/EI Non-Magnetic	Standard	S	•	•	•
TX2M25EM-6	1/2"	Si/EI Magnetic	Standard	S	•	•	•
TX2M25GM	3/4"	Si/EI Magnetic	Standard	S	•	•	•
5.00 MHz Bolt Gauge Transducers							
TX5M00AM-2	1/8"	Si/EI Non-Magnetic	Standard	S	•	•	•
TX5M00AM-3	1/8"	Si/EI Magnetic	Standard	S	•	•	•
TX5M00CM-7	1/4"	Si/EI Non-Magnetic	Standard	S	•	•	•
TX5M00CM-8	1/4"	Si/EI Magnetic	Standard	S	•	•	•
TX5M00DM	3/8"	Si/EI Magnetic	Standard	S	•	•	•
TX5M00EM-7	1/2"	Si/EI Magnetic	Standard	S	•	•	•
TX5M00EM-6	1/2"	Si/EI Non-Magnetic	Standard	S	•	•	•
TX5M00GM	3/4"	Si/EI Magnetic	Standard	S	•	•	•
10.00 MHz Bolt Gauge Transducers							
TX10M0AM-2	1/8"	Si/EI Non-Magnetic	Standard	S	•	•	•
TX10M0AM-3	1/8"	Si/EI Magnetic	Standard	S	•	•	•
TX10M0CM-4	1/4"	Si/EI Non-Magnetic	Standard	S	•	•	•
TX10M0CM-5	1/4"	Si/EI Magnetic	Standard	S	•	•	•

S - Standard Undamped Transducer