HTJY-80S Automatic Insulating Oil Dielectric Strength Tester (Three Cups)



I. Introduction

This equipment was designed on basis of GB-86"Oil-insulating testing", the process and result displayed by LCD, built-in EEPROM, can save 50 groups test results, all work can finished by mouse, test results printed by micro printer. This equipment is easy to operate, with powerful functions, stable and reliable, with strong anti-jamming ability, without death halt during the test.

II.<u>Features</u>

1. This process and test results are displayed by LCD.

2. Built-in EEPROM can store more than 50 groups test results.

3. All work can be finished by mouse, test results are printed by micro printer

4. This equipment is easy to operate, with powerful functions, stable and reliable, with strong antijamming ability, without death halt during the test.

III. Parameters

| Input voltage | AC 220V±10% |
|------------------------------------|--|
| Output voltage | AC 0~80KV |
| A cup, B cup, C cup | Can be arbitrarily chosen and combined |
| Voltage boosting speed | 2KV/s±10% |
| Accuracy degree | 3 |
| Number of times of continuous test | 1~6 |
| Stirring time | 0~99 seconds |
| Standing time | 0-9 minutes 59 seconds |
| Storage capacity | 50 groups data |
| Voltage limit setting | 20KV~70KV |
| Voltage withstand time | 0~10 minutes |
| Temperature | 5~40°C |
| Humidity | ≤80%RH |
| Dimension | 420×380×410mm3 |
| Weight | 28kg |

IV. Accessories

