



Product Bulletin



Follow us on Twitter @mountztorque

PB # 0043 (Rev 2) August 2013

www.mountztorque.com

New Models

flexPower
by mountz

Pistol Pulse Tools (Auto & Non-Shut Off)

Mountz adds 4 new large pulse tool models, increasing the product offering for the Flex Power tools.



Auto Shut-Off		Non Shut-Off		Drive Type	Torque Ranges		Free Speed (RPM)
Model	Item #	Model	Item #		lbf.ft	N.m	
FLEXS-180P	360157	FLEX-180P	360161	3/4" Sq Dr.	132.8 - 188	180 - 255	2700
FLEXS-200P	360171	FLEX-200P	360172	3/4" Sq Dr.	177- 332	240 - 450	3000

Specifications

Auto Shut-Off		Non Shut-Off		Weight		Noise Level dBa	Avg. Air Consumption		Hose Size mm
Model	Model	Model	Model	lbs.	kgs		m3/min. CMM	ft3/min CFM	
FLEXS-180P	FLEX-180P	FLEX-180P	FLEX-180P	8.4	3.8	86.0	0.73	25.6	11
FLEXS-200P	FLEX-200P	FLEX-200P	FLEX-200P	9.4	4.3	88.0	1.38	48.78	13

Note! Recommended air pressure is 85 PSI. Use a high quality air filter regulator and lubricator to ensure stable air pressure for optimal performance and for removal of moisture and other potential debris that can reduce the longevity and performance of pneumatic tools.

All specified torque ranges were established statically on a Mountz (TorqueLab LTT Series) torque meter at a dynamic air pressure of 85 PSI (Pounds per Square Inch). The specified results should be used as guidance only in tool selection. In general, the torque range will be lower based on type of joint, air pressure, extension bars and/or extended sockets. A pulse tool is a discontinuous tool and added adapters or extensions create a dampening effect, thus lowering torque values. Tool selection as well as set up is recommended to be validated on the actual joint by use of a suitable calibrated torque wrench. We recommend a quality Mountz digital torque wrench.