



RG316-DS Flexible Coax Cable FEP Jacket

Electrical Specifications

Description	Min	Тур	Max	Units
Frequency Range	DC		3	GHz
Impedance		50		Ohms
Velocity of Propagation		70		%
Operating Voltage (AC)			1,200	Vrms
Nominal Capacitance		29.39		pF/ft
		[96.42]		[pF/m]

Performance by Frequency Band

Description	F1	F2	F3	F4	F5	Units
Frequency	0.1	0.4	1	3		GHz
Attenuation, Typ	8 26.25	16.2 53.15	26.1 85.63	46.7 153.22		dB/100ft dB/100m

Mechanical Specifications

Diameter Weight 0.114 in [2.9 mm] 0.016 lbs/ft [0.02 Kg/m]

Min. Bend Radius (Installation)

0.591 in [15.01 mm]

Construction Specifications

Description	Material and Plating	Diameter					
Inner Conductor	Copper, Silver, 7 Strands	0.046 in [1.17 mm]					
Conductor Type	Solid						
Dielectric	PTFE	0.059 in [1.5 mm]					
First Shield	Silver Plated Copper Braid						
Second Shield	Silver Plated Copper Braid	Silver Plated Copper Braid					
Jacket	FEP	0.114 in [2.9 mm]					

Environmental Specifications

Temperature

Operating Range -55 to 200 deg C

Compliance Certifications (visit www.FairviewMicrowave.com for current document)

RoHS Compliant Yes

Plotted and Other Data

Notes:



Configuration:

- Flexible Cable
- 2 Shield(s)

Fairview Microwave 1130 Junction Dr. #100 Allen, TX 75013 Tel: 1-800-715-4396 / (972) 649-6678 Fax: (972) 649-6689 www.fairviewmicrowave.com

sales@fairviewmicrowave.com





RG316-DS Flexible Coax Cable FEP Jacket from Fairview Microwave has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order


Click the following link to obtain additional part information: RG316-DS Flexible Coax Cable FEP Jacket RG316DS

URL: http://www.fairviewmicrowave.com/rg316-ds-flexible-coax-cable-fep-jacket-rg316ds-p.aspx

to implem	nent improv	ements.	Fairview	/ Microwa	ave reserve	es the righ	nt to mak	ke such	changes	as requ	ired. Unles	s oth	nerwise
stated, al	l specificati	ons are	nominal.	Fairvie	w Microwa	ve does n	ot make	any rep	resentat	ion or v	warranty re	gard	ing the
suitability	of the par	t describ	ed hereir	n for any	particular particular	purpose,	and Fair	view M	icrowave	does n	ot assume	any	liability
arising ou	t of the use	e of any	part or do	ocument	ation.								







FAIRVIEW MICROWAVE INC. ALLEN, TX 75013 WWW.FAIRVIEWMICROWAVE.COM	NOTES: 1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL. 2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME. 3. DIMENSIONS ARE IN INCHES [mm].					
RG316-DS Flexible Coax Cable FEP Jacket	DWG NO RG316DS			CAGE CODE 3FKR5		
/	CAD FILE 120315	SHEET	SCAL	E N/A	SIZE A	5568