



## Specification

Model	SH-CH-100G
Air Circulation	Forced
Temp Range	Ambient +5°C to 70°C (Ambient + 9°F to 158°F)
Temp Control	Microprocess Digital P I D Membrane touch controller
Time Range	00.00 to 99HR 59MIN (MIN SEC) Selectable Digital Counter Timer
Temp Accuracy & Stability	±0.1°C
Temp Uniformity	±0.5°C
Capacity	100 L
Dimension Internal (WxDxH)	480x400x530(mm) 18.90x15.75x20.87(inch)
Dimension External (WxDxH)	625x580x870(mm) 24.61x22.83x34.25(inch)
Net Weight	51 Kg
Material Internal	Stainless Steel
Material External	Steel Plate with Powder Heating Coated
Shelves	Movable epoxy coated wire shelves 2 Supplied (15 Maximum)
Electrical Requirements 120V ,50/60Hz, 1Φ	5.0 A
Heater	600 W
Electrical Requirements 230V ,50/60Hz, 1Φ	2.6 A

## Feature

- Automatic reset function incoming power cut
- Buzzer on when set time arrived
- Door open alarm
- Electric leakage breaker
- Over temp controller

## Option

- Programmable Controller
- Digital Recorder
- 2CH Hybrid Recorder
- RS-485 interface
- RS-232C interface