

# KTM-15/150/250/1000

1.The torque meters are directly produced in Japan, authorized by Kilews Industrial Co., Ltd. ODM. Each product will be provided with an Adjustment Certificate and one year Warranty in normal using. Take Note! These measuring instruments could not be applied in testing the pneumatic screwdriver products and prohibited in measuring the torque exceeding maximum measuring range of torque meters.

2.Led can identify the test range of torque setting by needed user. If the result is not complying to torque range setting Light will be warred.

3.USB connector is only used for data output : it is convenient for user to work with computer.

4.Auto-zero can be selected and zero reset becomes unnecessary for user.

5.Automatically test values about maximum, minimum and mean.

## KTM-15/150/250/1000





## Product Spec

Model		KTM-250	KTM-150	KTM-15	KTM-6	KTM-50S
Measuring Ranges	(kgf.co m)	3.0~250.0	1.5~150.0	0.15~15.0	0.020-6	1-50
	(Lbf.in)	3.0~217.0	1.5~130.0	0.15~13.0	0.020-5.4	1-45.00
	(N.m)	0.30~25.00	0.15~15.0	0.015~1.500	0.002-0.6	0.1-5.00
Accuracy		±0.5%				
Power Supply		4.8VDC(Ni-MH chargeable battery 1.2VX4 cell 1650mAh)			1.2V batteryX5	
Charging Time		From empty -3 hours			With in 8 hours	
Operation Time		About 12 hours				

Battery Life	Chargeable for 300 time or more. However, it varies depending on operating conditions.				
Size(mm)	160(W)X210(D)X45(H)	230(W)X125(D)X65(H)		160(W)X125(D)X55(H)	123(W)X230(D)X65(H)
Weight(kg)	2	1.8		1.2	2
Exclusive Charger	Input : AC100v~240V 50/60Hz Output : DC12V 500mA				Input: AC120V, 220-240V
Accessory	Torque measuring adaptorX1 AJ-250	Torque measuring adaptorX3 AJ-150/AJ-50/AJ-15K	Torque measuring adaptorX2 AJ-15/AJ-3	Torque measuring adaptor X1 SJ-3	Torque measuring adaptor X1 J-50S