

AM4115ZT



The AM4115ZT, with the exceptional image quality of Dino-Lite Edge, is designed to meet more professional needs. The freely adjustable polarizer further extends its versatility along with the exchangeable front cap design.

## Overview



### High optical resolution

With the state-of-the-art lens design, the Dino-Lite Edges series delivers matchless image quality with stunning sharpness, least aberration, and least vignetting throughout the whole magnification range.



### Convenient flexible magnification

The Dino-Lite is capable of variable magnification with a range of 20~220x depending of working distance by simply zooming in or out with just a rotating dial.



### Polarizer

To many applications, it is inevitable to have reflection on the surface resulting from the built-in illumination. The freely adjustable polarizer helps to reveal more detail or to enhance the contrast on the surface by reducing or eliminating the reflections. For applications such as optical mineralogy requiring transmitted polarizing illumination, the Dino-Lite back-light pad (BL-ZW1) is optional to be used with all Dino-Lite polarizer models.



### Adaptable cap design

This model features a detachable and interchangeable front cap that extends its range of use, as different caps are available for various applications. Removing the front cap provides greater working distance and access to the full magnification range.

#### Information about working distance and field of view

M	WD	FOV (x)	FOV (y)	DOF
20	60.2	19.5	15.6	2.5
30	33.5	13	10.4	1.8
40	20.9	9.8	7.8	1.5
50	13.9	7.8	6.3	
60	9.7	6.5	5.2	
70	7.1	5.6	4.5	1.0
80	5.5	4.9	3.9	
90	4.5	4.3	3.5	
100	4.1	3.9	3.1	
110	4	3.6	2.8	
120	4.1	3.3	2.6	
130	4.5	3	2.4	
140	5	2.8	2.2	
150	5.6	2.6	2.1	
160	6.3	2.4	2	
170	7.1	2.3	1.8	
180	8	2.2	1.7	
190	8.9	2.1	1.6	
200	9.9	2	1.6	
210	10.9	1.9	1.5	
220	11.9	1.8	1.4	0.1

M = magnification rate    WD = working distance (without front cap)    FOV = field of view  
DOF = depth of field    Unit = mm

#### Specification

Model : AM4115ZT Dino-Lite Edge

Interface : USB 2.0

Product Resolution : 1.3M pixels (SXGA)

Magnification Rate : 20x~220x

Sensor : Color CMOS

Frame Rate : Up to 30fps

- Save Formats:

+ Image:

DinoCapture2.0: BMP, GIF, PNG, MNG, TIF, TGA, PCX, WBMP, JP2, JPC, JPG, PGX, RAS, PNM

DinoXcope: PNG, JPEG+ Movie:

DinoCapture2.0: WMV, FLV, SWF

DinoXcope: MOV

Microtouch : Touch sensitive trigger on the microscope for taking pictures

Lighting : 8 white LED lights switched on/off by software

Polarizer : Yes

Measurement Function : Yes

Calibration Function : Yes

Operating System Supported : Windows 10, 8, 7, Vista, XP; Mac OS 10.9 or later

Unit Weight : 100g

Unit Dimension : 10.3cm (H) x 3.2cm (D)

Package Dimensions : 16cm (L) x 16cm (W) x 6cm (H)

#### Interchangeable Front Caps



N3C-D / Diffuser Cap

This cap diffuses the LED light.



N3C-D2 / Opal Diffuser Cap  
This cap diffuses the LED light.



N3C-E / Extended Open Cap  
Dino-Lite Edge (stand type) will focus at approximately 200x when the cap touches surface.



N3C-L / Long Cap  
This cap is useful to adjust the working focus of Dino-Lite Edge at lower magnification.



N3C-O / Open Cap  
This is the standard cap for normal usage.



N3C-S / Sidelight Cap  
This cap creates images with more depth and texture.



N3C-C / Close Cap  
This cap protects the lens and LED lights from contamination of dust, debris, or moisture.

