

QC-115A Bursting Strength Tester

Standard

Description

This Bursting Strength Tester uses oil pressure to break specimen through rubber film. This tester is used to test the breaking strength of paper, leather, textile etc.

Appearance



Specification

Pressure indicate	Pressure Gauge
Borken strength idication	Friction pointer
Speed of pressurization	95 ± 10 ml/min
Grip force	Pressure gauge can be set the grip force
Hydraulic oil	Glycerin 85%, distilled water 15%
	upper: 30.48mm ± 0.03mmΦ
Diameter of clamping	lower: 31.75mm ± 0.25mmΦ
Power	Single phase, 110V/60Hz or 220V/50Hz
Weight	60 Kg
Accessories	Rubber diaphragm, Standard aluminium foil, wrench,certificate, operation manul , Glycerin
Capacity	5、10、20、50Kg/cm ² (choose two)
Dim.	35 × 53 × 50 cm

* Cometech reserves ultimate modification right of product specification.

1st Version 2016



COMETECH TESTING MACHINES CO.,LTD.
No.49, Ln.39, Liancun Rd., Fengyuan Dist., Taichung City 42082,
Taiwan
Tel/886-4-25368881 Fax/886-4-25368883
[e-mail/info@come-tech.com.tw](mailto:info@come-tech.com.tw) www.come-tech.com.tw