

**SB 18 (602245560) Cordless hammer drill**

**18V 2x2Ah Li-ion; Charger SC 30 (220-240 V / 50 - 60 Hz); Plastic Carry Case**

Order no. 602245560

EAN 4007430331465



Product may differ from Image

- Light, compact cordless hammer drill with extremely compact design for versatile use
- Hammer drill function for drilling in masonry
- Integrated working light to illuminate the contact area
- With handy belt hook and bit case which can be fixed either on the right or left side
- Battery packs with capacity display for checking the charge status
- Ultra-M technology: highest performance, gentle charging and 3 years of warranty on the battery pack.

## Technical data

### Characteristics

|                                 |                               |
|---------------------------------|-------------------------------|
| Type of battery pack            | Li-ion                        |
| Battery voltage                 | 18 V                          |
| Battery pack capacity           | 2 x 2 Ah                      |
| Maximum torque - soft           | 24 Nm / 212 in-lbs            |
| Maximum torque, hard            | 48 Nm / 425 in-lbs            |
| Adjustable torque               | 0.5 - 4.5 Nm // 4 - 40 in-lbs |
| Drill-Ø masonry                 | 10 mm / 3/8 "                 |
| Drill Ø steel                   | 10 mm / 3/8 "                 |
| Drill-Ø soft wood               | 20 mm / 3/4 "                 |
| No-load speed                   | 0 - 450 / 0 - 1600 rpm        |
| Maximum impact rate             | 24000 bpm                     |
| Chuck capacity                  | 1 - 10 mm // 1/32 - 3/8 "     |
| Weight (including battery pack) | 1.41 kg / 3.1 lbs             |

### Vibration

|                              |                      |
|------------------------------|----------------------|
| Drilling in metal            | 2.5 m/s <sup>2</sup> |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |
| Impact drilling concrete     | 23 m/s <sup>2</sup>  |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |

### Noise emission

|                              |          |
|------------------------------|----------|
| Sound pressure level         | 86 dB(A) |
| Sound power level (LwA)      | 97 dB(A) |
| Uncertainty of measurement K | 3 dB(A)  |

## Scope of delivery

Keyless chuck  
 Charger SC 30  
 Charger SC 30  
 Plastic carry case  
 Belt hook and bit case  
 2 Li-Power battery packs (18 V/2.0 Ah)