



深圳市宏之都科技有限公司

HONGDU TESTING EQUIPMENT CO., LTD.

## HD-950B Pressure tester



This instrument is suitable for all kinds of two-core molded plug wires, such as speaker cables, headphone cables, power cords, etc. The electrical properties required: short circuit, conduction, insulation, etc. The instrument is composed of integrated circuits and is indicated by instruments.

### Technical Parameters:

Serial number	Project	Specifications	
1	Voltage test	The output voltage	0-5KV 50mA
		rated power	800VA/5KV
		Wave shape	50/60Hz AC sine wave
		Voltage calibration	±5%
		Switch	Zero level shift
		testing time	60S
2	Voltage finger Display head	Ratio	1: 50
		Level	1. 5 CLASS
		Accuracy	±3%

3	Failure judgment Display head	Judgment	* The measured value is larger than the reference value. * The output voltage is cut off to give a failure signal.
		Leakage current setting	0. 5、 1、 3、 5、 10、 50mA。
		Judgment accuracy	±5%Set value now
		Calibration	Pure resistance load series R M S truth table test
		Check no load The output voltage	about 400V
4	Size	Dimensions	370*300*170
		Packing shape	420*360*195
5	Weight		about 25KG
6	Input voltage		220VAC±10%