

THE ASIA'S
TECHNOLOGY LEADER

A SINGLE-SOURCE SUPPLIER OF STRAPPING MACHINE

THE ASIA'S TECHNOLOGY LEADER

A SINGLE-SOURCE SUPPLIER OF STRAPPING MACHINE



[Home](#) > [PRODUCTS](#) > [Automatic Strapping Machines](#) > TP-702PS Mercury with Dual Pneumatic Press (stainless steel frame SUS304)

PRODUCTS

- [Strapping Tools](#)
- [Semi-Auto Strapping Machines](#)
- [Automatic Strapping Machines](#)
- [Fully Automatic Strapping Machines](#)
- [Corrugated Strapping Machines](#)
- [Print Media Strapping Machines](#)

TP-702PS Mercury with Dual Pneumatic Press (stainless steel frame SUS304)



TP-702PS is a high-speed automatic strapping machine with stainless steel frame (SUS 304). It equips with dual pneumatic press for strapping compressible materials. It is ideal for moist working environment, such as meat, seafood, poultry, and agricultural processing plants.

[? INQUIRY](#)

Features

- Robust & compact mechanical strapping head
- Free access to strap guides (*patents registered*)
- Dual pneumatic press
- Waist-high auto strap feeding
- Waist-high quick coil change (*patents registered*)
- Turnable operating control panel
- Auto strap ejector
- Dispenser release switch
- Sensor controlled heater
- Low voltage
- Strap end ejector
- Front foot bar switch
- Adjustable table height between 820 mm and 920 mm

Options

- Photo-eye switch
- Rear foot bar switch
- Foot pedal switch
- Lower adjustable table height (770-820 mm)
- Safety guards
- Stainless steel frame SUS 304

Green Tech

Technical Data

Capacity	Up to 47 cycles/minute (TP-702PS-59) Up to 44 cycles/minute (TP-702PS-12)
Strap Width	5 mm, 6 mm, or 9 mm (TP-702PS-59) 12 mm (TP-702PS-12)
Tension Range	1 to 32 kg (TP-702PS-59) 1 to 55 kg (TP-702PS-12) (Higher tension is on request)
Weight	224 kg (TP-702PS-59) 226 kg (TP-702PS-12)
Electrical Requirements	110V, 220V, 230V, 240V 50/60Hz 1PH

**ALL PRODUCTS ARE WELL MADE BY OUR ISO 9001 CERTIFIED FACTORY IN
TAIWAN, WITH PRIDE.**

📍 15F-1, NO. 17, SEC. 1, CHENGDE ROAD, TAIPEI 103, TAIWAN ✉ transpak@tran  com.tw

☎ TEL +886 2 2555 2515 📠 FAX +886 2 2555 2516